

4-20mA
Series

RTD Probe w/4-20mA Transmitter



Measure extreme temperatures

The RTD probe with 4-20mA transmitter can be used to measure the temperature in extreme environments. Part number FGD-0240 is calibrated to operate over the range -200° to 35°C. Part number FGD-0240-SPEC can be customized at time of order to operate over any range between -200° and 204°C. The sensor will need a 24VDC power supply to operate (Part # FGD-0070)

TECH SPECS

Name	RTD Probe w/4-20mA Transmitter
Sensor Temperature Range	-328° to 399°F -200° and 204°C Custom transmit ranges can be specified at time of order
Connection	Hardwired
RTD Element	PT100 - 385ALPHA - CLASS - B
Dimensions	1" stainless steel RTD probe with 10' cable
Sensor Series	4-20mA Series
Notes	Element tolerance to IEC 60751 edition 2.0, par 5.1.2

All specifications subject to change without notice

Product Name

Part Number

RTD Probe w/4-20mA Transmitter (-200° to 35° C) FGD-0240

RTD Probe w/4-20mA Transmitter (User Specified Range) FGD-0240-SPEC



Family owned and made in the USA since 1985

901 Tryens Road

Phone: 877-373-2700

Aston, PA 19301

Web: sensaphone.com

